



Professional Speaker Cable

Technical Specifications:

Model		1920	2420	2419	4012
Colour		GRAY BLACK/WHITE	GRAY BLACK/WHITE	TRANSPARENT	RED/BLACK
No. of Cable		1 PAIR	1 PAIR	2 CORE	2 CORE
Conductor	Material	TINNED COPPER	TINNED COPPER	TC/BC	BARE COPPER
	No./mm	19/0.2	24/0.2	140/0.12	40/0.12
	AWG/mm sq.	20/0.6	19/0.75	15/1.58	25/0.45
Insulation	Nom_thickness (mm)	0.6	0.6	0.98	
	Nom. O.D(mm)	2.2	2.3	3.6X7.2	2.5X5.0
Sheath	Nom_thickness (mm)	0.8	0.6		
	Nom. O.D(mm)	5.8	6.0		
Max.DC Resistance /km 20°C		34.6	27.5	10.2	43

Features:

- INTERCOM/PA SYSTEMS
- SOUND / AUDIO SYSTEMS



Security Control Cable

Technical Specifications:

Model No.	7024	7026	7028	70212
No. (mm)	4x0.7/0.2mm	6x0.7/0.2mm	8x0.7/0.2mm	12x0.7/0.2mm
No. of Core	4	6	8	12
Weight (Nom.)	18Kg/ Km	25 Kg/Km	30Kg/Km	37 Kg/Km
Outside Dia. (Nom.)	3.6(+/-)0.3	4.3(+/-)0.3	4.6(+/-)0.3	5.4(+/-)0.3
Packaging	100/200 yards	100/200yards	100/200 yards	100/200 yards
Jacket Color	white	white	white	white

Features:

- POWER LIMITED CONTROLS
- SINGLE LINE TELEPHONE
- SECURITY SYSTEMS